

12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

TIME CONTROLS WITH ENHANCED TIMING RANGE

Inventor: William P. Tanguay

TIME CONTROLS WITH ENHANCED TIMING RANGE
CROSS-REFERENCE TO RELATED APPLICATION

The present invention is based on and claims priority to U.S.
Provisional Application Serial No. 60/218,406, filed July 14, 2000.

BACKGROUND OF THE INVENTION

The present invention generally relates to time controls, such as repeat cycle timers or interval timers. More specifically, the present invention relates to a time control that includes a non-linear cycle time setting and a duty cycle setting such that the time control provides a broad range of timing capability.

In the early days of timer design, mechanical timers were available that were driven by synchronous AC motors to provide a means to generate "repeat cycle timing" of a load. These same types of synchronous motors also provided a means to generate "interval timing". The time base in each of the time controls was generally set by the motor and a set of appropriate gears to slow down the motor rotation speed to the desired final speed. In the early days of timer design, adjustable mechanical cams and similar apparatus could be attached to revolving pieces of the control and these links enabled the user to adjust the duty cycle or interval time. However, the basic time base was very fixed and related to the final rotational speed of the "setting wheel".

As timer design evolved, it became advantageous for designers and manufacturers to use analog oscillators as the adjustable time base for various time keeping functions. One common type of analog oscillator coupled a potentiometer to a knob with a printed time scale showing the approximate time on the face plate of the timer. The printed time scale served as a means to enable a widely variable time base that was not expected to be repeatable or extremely accurate for both repeat cycle times and interval timers.

As time keeping technology continued to evolve, it became advantageous for designers and manufacturers to use digital countdown circuits that were synchronized to accurate crystal time bases or an AC power line. Digital countdown circuits are typically found in either discrete digital logic components or can be implemented by software running within a microcomputer.

In either case, these techniques offered a means to provide an accurate and repeatable timing function for both the repeat cycle timers and interval timers.

As shown in Fig. 1, a conventional repeat cycle timer can include two rotary knobs 12 and 14 that allow a user to set an "ON" time and an "OFF" time independently of each other. In the sample of the prior art illustrated in Fig. 1, each of the rotary time setting knobs 12 and 14 includes a linear time range spanning between 30 seconds and 15.5 minutes in thirty-two equally spaced steps of 30 second resolution. Thus, when utilizing the repeat cycle timer 10 illustrated in Fig. 1, the user can set a time base for the complete cycle of a minimum of 60 seconds to a maximum of 31 minutes and a duty cycle of 3.3% to 96.8%. In this control configuration, the user can select a desired repeating time base by summing the "ON" time and the "OFF" time of each rotary knob 12 and 14. Similarly, the duty cycle (or active load percentage) can be set comparing the ratio of the "ON" rotary knob 12 and the "OFF" rotary knob 14.

When utilizing the rotary timer 10 of the prior art, if the user needs a repeating time base of one minute, each knob of the cycle time could be set to 30 seconds. At this minimum value, there would be only one percentage setting available - 50% duty cycle since the minimum resolution for each knob 12 and 14 is 30 seconds. In a second example, if the repeating time base was required to be two minutes, the sum of the settings of both knobs 12 and 14 could be set for that two minute requirement. In the prior art repeat cycle timer 10 illustrated in Fig. 1, three options would then be 30 seconds "ON" and 90 seconds "OFF" (25% duty cycle), 60 seconds "ON" and 60 seconds "OFF" (50% duty cycle), and 90 seconds "ON" and 30 seconds "OFF" (75% duty cycle). These two examples illustrate that the ultimate flexibility of the variable percentages is limited by the necessary choice of the time base. Secondly, unless the user carries a calculator, the mental math required to calculate the percentage duty cycle may be quite difficult. For example, 3.5 minutes "ON" and 13 minutes "OFF" requires a mental calculation of $(3.5)/(3.5 + 13.0) = 21.2\%$.

Therefore, it is an object of the present invention to provide a time control unit that allows the user greater flexibility, convenience and independence in setting both the repeating time base and the percentage duty cycle. It is a further object of the invention to provide a time control unit that includes one knob

to define a timing range that grows in a non-linear manner from a relatively small minimum time to a relatively large maximum time. Further, it is an object of the present invention to provide a second knob that allows the user to define the duty cycle in a non-linear manner, preferably with greater resolution between 1% and 10% and 90% to 100% duty cycle. Further, it is an object of the present invention to present a time control unit that presents the user with an easy to understand determination of both the repeating time base and the load duty cycle.

SUMMARY OF THE INVENTION

The present invention relates to a time control unit that has a time base dial to set overall cycle time and a duty cycle dial to control the percent of the cycle time that a load is energized.

The time base dial of the time control unit is used to set the overall cycle time and includes a plurality of individual time base settings that increase in a non-linear manner from a minimum setting to a maximum setting. In one specific example of the invention, the values for each discrete position of the time base dial can be used to set the cycle time between a low value of 15 seconds and a high value of 24 hours. The individual settings between the high and low value generally increase in an exponential manner such that several decades of values can be represented over the thirty-two discrete settings for the time base dial.

The time control unit further includes a duty cycle dial that allows the user to accurately set the percentage of the cycle time which the load is activated. The duty cycle dial includes a plurality of discrete positions that allow the user to accurately determine the percentage of time the load is activated during the overall cycle time. The individual positions for the duty cycle dial can increase from a minimum setting to a maximum setting in either a linear manner or a non-linear manner, depending upon the user requirements. In one embodiment of the invention, the settings for the duty cycle dial include higher resolution near the 0% and 100% settings and a lower resolution near the 50% setting. Alternatively, the settings can be selected to increase generally exponentially to provide very high resolution near either the 100% or 0% settings, depending upon the user requirements.

The time control unit of the present invention includes a control unit that calculates and controls the cycle time and duty cycle based upon the settings of the time base dial and the duty cycle dial. The control unit polls each of the rotary switches that serve as the time base dial and the duty cycle dial to
5 determine the current position of each dial. Based upon the current position of the dial, the control unit counts the required times and operates a relay circuit coupled to the control unit. The relay circuit, when closed, provides power to a load. The control unit can be programmed to allow the settings of both the time base dial and the duty cycle dial to be adjusted to any selected values such that
10 the time control unit of the present invention can provide the user with extremely accurate and variable settings for both cycle time and the duty cycle.

Various other features, objects and advantages of the invention will be made apparent from the following description taken together with the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

The drawings illustrate the best mode presently contemplated of carrying out the invention.

In the drawings:

Fig. 1 is a front view illustrating a representative time control unit of
20 the prior art;

Fig. 2 is a front view of a time control unit of the present invention having a pair of rotary knobs that control the repeating time base and the duty cycle;

Figs. 3a and 3b are detailed circuit schematics illustrating the
25 operating configuration for the time control unit of the present invention;

Fig. 4 is a graph illustrating the repeating time base for each of the discrete positions equally spaced around the rotary time base dial of the time control unit;

Fig. 5 is a logarithmic graph illustrating the repeating time base
30 value for each of the discrete positions of the rotary time base dial of the time control unit;

Fig. 6 is a graph illustrating two separate, alternate settings for the discrete positions of the rotary cycle time dial that sets the duty cycle percentage for the time control unit of the present invention;

Fig. 7 is a graph illustrating a further alternate setting for the discrete positions for the rotary cycle time dial that sets the duty cycle percentage in which the cycle time varies on an exponentially increasing percentage; and

Figs. 8a and 8b are tables illustrating the time base and duty cycle values for each of the discrete positions of the rotary dials on the time control unit of the present invention;

DETAILED DESCRIPTION OF THE INVENTION

Referring first to Fig. 2, there is shown a time control unit 16 of the present invention. The time control unit 16 includes an internal relay circuit that is opened and closed by the electronics contained within the time control unit 16. The internal relay within the time control unit 16 is coupled to an electronic device or load that is desired to be cycled "ON" and "OFF" for a selected duty cycle over a predetermined repeating time base. As can be seen in Fig. 2, the time control unit 16 of the present invention includes a rotary time base dial 18 and a rotary duty cycle dial 20 each of which are rotatable over 360°.

The time base dial 18 allows the user to select between thirty-two individual settings that define the length of the time base for each cycle controlled by the time control unit 16. The time base dial 18 includes a printed display 22 having a series of markings around the outer circumference of the time base dial 18 that clearly display to the user the length of time represented by each discrete position of the time base dial 18. In the preferred embodiment of the invention, the time base dial 18 is a digital switch or encoder that includes thirty-two discrete positions around the outer circumference of the time base dial 18. Each of the thirty-two positions for the time base dial 18 is defined by a detent such that the time base dial 18 snaps into one of the defined positions around the outer circumference, each of which is identified by the printed display 22.

As can be seen in Figs. 2 and 4 and the table of Fig. 8a, the thirty-two discrete positions for the time base dial 18 define a timing range that grows non-linearly from a minimum time base setting to a maximum time base setting. Although the specific time range of 15 seconds to 24 hours is illustrated in the

preferred embodiment of the invention, it should be understood that the selected minimum and maximum values for the time base settings can be modified, as will become apparent in the discussion below.

Referring now to Fig. 5, it can be seen that the values for the time base dial 18 for each of the thirty-two positions of the time base dial 18 increase in a non-linear, generally exponential fashion. The use of the generally exponential increase in the value of the time base settings around the outer circumference of the time base dial 18 allows the time control unit 16 to be used over a much larger range of time base values (several decades in the illustrated embodiment) as compared to the prior art cycle timers that included a linear progression of time base values around the outer circumference of the time base dial.

Referring back to Fig. 2, the duty cycle dial 20 of the time control unit 16 also includes a printed display 24 that identifies the thirty-two discrete positions for the duty cycle dial 20. Like the time based dial 18, the duty cycle dial 20 is a digital switch or encoder that includes thirty-two discrete positions around its outer circumference. Each of the thirty-two positions for the duty cycle dial 20 is defined by a detent such that the duty cycle dial 20 snaps into one of the defined positions around the outer circumference, each of which are identified by the printed display 24.

As discussed previously, the duty cycle dial 20 allows the user to select the percentage of time the device attached to the time control unit 16 is turned on during the cycle time set by the time base dial 18. For example, if the time base dial 18 is set for a cycle time of ten minutes and the duty cycle dial 20 is set for 35%, the device attached to the time control unit 16 will be activated for the first 3.5 minutes, or 35%, of the ten minute cycle time. The load will then be deactivated for the next 6.5 minutes of the ten minute cycle. After the remaining 6.5 minutes of the cycle time expire, the time control unit 16 will begin a new cycle and the device will again be operated for the first 3.5 minutes of the second cycle.

As can be seen in Fig. 2, the duty cycle dial 20 includes a constant "OFF" position 26 and a constant "ON" position 28. The remaining thirty discrete positions between the constant "OFF" 26 and the constant "ON" 28 can be divided using several different methods. For example, in a first contemplated

configuration, the thirty positions between the constant "OFF" position 26 and the constant "ON" position 28 can be divided in a generally linear manner, as illustrated by the linear percentage line 30 shown in Fig. 6. As the linear percentage line 30 indicates, each of the discrete settings for the duty cycle dial 20 increase in a linear manner from the second position to the thirty-first position. The linear percentage line 30 is also tabulated in Fig. 8b for the thirty-two discrete positions of the duty cycle dial 20. The linear percent progression around the duty cycle dial 20 allows the user to increase the duty cycle by a selected amount for each clockwise position increase of the duty cycle dial 20.

In a second improved and preferred embodiment of the invention, the thirty positions for the duty cycle dial 20 between the constant "OFF" 26 and the constant "ON" 28 are arranged in a non-linear progression such that enhanced resolution is available near both the 0% and the 100% positions. The non-linear calibration for the duty cycle dial 20 is illustrated by the non-linear percentage curve 32 of Fig. 6. As can be seen in Fig. 6, the non-linear percentage curve 32 has a generally "S" curve with increased resolution between approximately the first and tenth positions and the 22nd - 32nd positions of the duty cycle dial. The duty cycle dial 20 has lower resolution centered around the 50% duty cycle setting, as can be seen in Fig. 6. The "S" curve of the non-linear percentage line 32 allows the user to have greater flexibility in selecting the percentage of the duty cycle at percentages near 0% and 100%. The selection of the "S" curve is based upon the desire of typical users to have a large number of choices for selecting the percentage of the time base for the duty cycle near the minimum and maximum values. The specific percentages for the second, preferred embodiment of the invention are shown in tabular form in Fig. 8 and in graphic form on the printed display 24 illustrated in Fig. 2.

Referring now to Fig. 7, there is shown a third embodiment of the invention in which the thirty settings around the duty cycle dial 20 are calibrated using an exponential percentage line 33. As can be seen by examining Fig. 7 and the tabular presentation of Fig. 8, the resolution of the duty cycle dial 20 is dramatically increased near the 0% or "OFF" position 26. Specifically, the first twenty-two settings around the outer circumference of the duty cycle dial 20 represent 10% of the duty cycle, while the remaining ten settings represent the

other 90% of the duty cycle. In this manner, the resolution near 0% is greatly increased while the resolution near 100% is very low. Additionally, it is contemplated by the inventor that the exponential percentage curve 33 illustrated in Fig. 7 could be reversed such that the timer would have very enhanced resolution near 100% and have very low resolution near 0%, depending upon the requirements of the user.

Referring now to Figs. 3a and 3b, there is shown the detailed circuit schematic that controls the operation of the time control unit 16 of the present invention. The time control unit 16 is controlled by a control unit 36. Control unit 36 of the present invention is Model No. 16C54-RCI/P, available from Microchip Corporation. The control unit 36 is operated by a power supply 38, which is preferably +5 volts DC. The control unit 36 includes an internal clock that operates based upon a real time clock signal received on line 40. The real time clock signal received on line 40 is derived from the 60 Hz AC power supply connected to the time control unit and used to operate the load connected to the time control unit. The real time clock signal present at line 40 is a very accurate signal that allows the control unit 36 to provide dependable and accurate timing control.

The control unit 36 is connected to a first rotary switch 42, which functions as the time base dial, and a second rotary switch 44, which functions as the duty cycle dial. Each of the rotary switches 42 and 44 includes five output lines that each represent a digital bit. The five output lines allow each of the rotary switches 42 and 44 to provide a 5-bit digital signal to the control unit 36. The 5-bit output signal from each of the rotary switches 42 and 44 allows each of the rotary switches to define the thirty-two individual positions of both the time base dial and the duty cycle dial. The output of each of the rotary switches 42 and 44 is determined by the position of the rotary dial in both the time base dial and the duty cycle dial.

During operation of the time control unit, the control unit 36 periodically applies a high signal to the output pin 45, which is connected to the base of transistor 46 through the resistor 48. When a high signal is applied to pin 45, transistor 46 becomes saturated such that pin 50 of rotary switch 44 is essentially grounded. At the same time, the pin 52 of rotary switch 42 receives

the high signal from output pin 45. The high value of pin 52 of rotary switch 42 signals the rotary switch 42 to transmit a digital binary signal to control unit 36. Thus, when pin 45 of control unit 36 is high, the control unit 36 polls the rotary switch 42 to determine the position of the time base dial.

5 When the high signal is removed from pin 45 of the control unit 36, the rotary switch 42 stops transmitting its five bit binary signal. At the same time, the low signal is applied to the base of transistor 46 which causes the transistor 46 to act as an open circuit. The open circuit results in voltage VL is applied to pin 50 of the rotary switch 44. The high value at pin 50 causes the rotary switch
10 44 to send a binary signal representing the position of the duty cycle dial to the control unit 36. In this manner, the control unit 36 alternately polls each of the rotary switches 42 and 44 to determine their current position.

Control unit 36 includes internal programming that allows the control unit to have a time base value assigned to each discrete position of the rotary
15 switch 42 and a duty cycle percentage assigned to each discrete position of the rotary switch 44. Thus, the specific values for each setting of both the time base dial and the duty cycle dial can be easily programmed into the control unit 36 and can be configured to create time control units having differing operating characteristics.

20 In order to determine the selected time base value and the selected duty cycle value, the control unit 36 simply determines the current position of both of the rotary switches 42 and 44 and compares these current positions to the table of values stored within the control units internal programming. After
25 determining the position of both of the rotary switches 42 and 44, the internal timing structure within the control unit 36 provides an accurate time count to create both the overall cycle time and operates the load for the selected duty cycle. Since each of the rotary switches 42 and 44 generates a digital signal based upon the plurality of discrete settings, the control unit 36 provides an extremely accurate time count based upon the user's selection.

30 The control unit 36 is connected to a conventional relay circuit 54, which is in turn connected to the control the load 56. The control unit 36 generates a high signal on pin 57 to activate the relay circuit 54 and thus turn on

the load 56. The high signal on pin 57 of the control unit 36 is controlled by the internal programming and timer within the control unit 36.

The control unit 36 is connected to a green LED 58 and a red LED 60. The green LED 58 is activated when the load 56 is turned on, while the red LED 60 is activated during the remaining portion of each duty cycle when the load 56 is inactive.

As can be understood by the circuit diagram of Fig. 3, each setting on both the time base dial and the duty cycle dial, which correspond to the rotary switches 42 and 44, is a non-ambiguous and extremely accurate setting that sends a digital 5-bit signal to microcontroller 36. Based upon these extremely accurate settings for both of the rotary switches 42 and 44, the microcontroller 36 digitally calculates the time values selected by the time base dial and the duty cycle dial. In this manner, the time base value and duty cycle percentage are highly accurate and extremely repeatable.

Referring back to Fig. 2, the user is presented with a pair of dials 18 and 20 that each include an easy to understand printed display that allow the user to easily determine both the time base of a complete cycle and percent the load will be on during the time base cycle. In the embodiment of the invention illustrated in Fig. 2, the user is presented with an accurate time control unit that has an exponential range of settings that spans several decades for the time base range. Additionally, the user is presented with a duty cycle dial that presents the user with a non-linear setting having higher resolution near the 0% and 100% settings and the lower resolution around the 50% duty cycle.

Although the present invention is illustrated in the Figures for a repeat cycle timer including both a time base dial 18 and a duty cycle dial 20, it is contemplated by the inventor that the concept of including a non-linear time range assigned to the thirty-two discrete positions of each dial could also be applied to a non-repeating, "one shot" timer. Such a timer is typically used for creating a delay before turning on a device or delaying the shutdown of one electric device compared to another. A "one shot" timer would include a single time base dial that includes discrete time settings separated from each other in a non-linear manner, similar to the time settings on the time base dial 18 of Fig. 2. For example, a time base dial that includes non-linear spacing between the discrete

time settings would allow the time dial to create time representations between five seconds and three hours.

- Various alternatives and embodiments are contemplated as being within the scope of the following claims particularly pointing out and distinctly
- 5 claiming the subject matter regarded as the invention.